



Double-Sided Hanging Holographic Invisible LED Poster		
Model	750×1339	1000 × 1508
Module		
Pixel Pitch	Horizontal: 3.91mm/Vertical: 3.91mm	
Pixel Density	65536dot/ m²	
Visual Transparency	> 80%	
Module Size	750mm×1208mm	1000mm×1508mm
Overall Module Size	765mm×1350mm×96mm	1065mm×1650mm×96mm
LED Type	2121 (Integrated light drive)	
Resolution Ratio	192×300pix	256×376pix
LED Control System	Synchronous/Asynchronous	
Brightness	White balance brightness ≥3500cd/m²; Automatically adjust and manually adjust according to ambient brightness	
Viewing Angle	Horizontal 160, Vertical 140	
Display Thickness	3.6mm	
Resumable Transmission	Supported	
Average Lifespan	≥ 100000 hours	
Gray Scale	≥ 16(bit)	
White Field Color Temperature	5500K-15000K (adjustable)	
Drive Mode	Static	
Atenuation Rate	2 years below 0.05%	
Average Fault-Free Working Time	≥ 10000 hours	
Maximum Power Consumption	1335W/ m²	
Average Power	534W/ m²	
Power Supply Requirements	110V ~ 220V±10%; AC50HZ, three-phase five-wire	
Operation Temperature	-20℃ ~ +50℃	
Working Humidity	20% RH ~ 85% RH, no condensation	
Storage Temperature	-20℃ ~ +60℃	
Storage Humidity	10%RH ~ 85%RH, no condensation	
Installation Method	Vertical	
Packaging Method	Cardboard Case/ Plywood Case / Flight Case	

**Declaration: The relevant parameters in the table are updated in real time, and the data is for reference only. No further notice will be given if there are any upgrades.**