







Holographic Vitra Series						
LED Driving Method	Integrated LED and Driver		Separate LED and Driver			
Model	IVin-3.9-500R	IVin-3.9-1000R	IV3.9-500R	IV3.9-1000R	IV4.8-500R	IV4.8-1000R
Module						
Pixel Pitch	Horizontal: 3.91mm/Vertical: 3.91mm				Horizontal: 4.8mm/Vertical: 4.8mm	
Pixel Density	65536dot/ m²				43264dot/ m²	
Visual Transparency	>80%		>70%			
Module Size	1000mm×250mm	1000mm×250mm	1000mm×250mm	1000mm×250mm	1000mm×250mm	1000mm×250mm
Overall Module Size	1000mm×500mm×73mm	1000mm×1000mm×73mm	1000mm×500mm×73mm	1000mm×1000mm×73mm	1000mm×500mm×73mm	1000mm×1000mm×73mm
LED Type	SMD2121		SMD1415		SMD1921	
Weight	3KG	6KG	3.5KG	7KG	3.38kg	6.74kg
Resolution Ratio	256×128pix	256×256pix	256×128pix	256×256pix	208×104pix	208×208pix
LED Control System	Synchronous/Asynchronous					
Brightness	White balance brightness 4000cd/m²; Automatically adjust and manually adjust according to ambient brightness	White balance brightness 4000cd/m²; Automatically adjust and manually adjust according to ambient brightness	White balance brightness 4500cd/m²; Automatically adjust and manually adjust according to ambient brightness	White balance brightness 4500cd/m²; Automatically adjust and manually adjust according to ambient brightness	White balance brightness 3500cd/m²; Automatically adjust and manually adjust according to ambient brightness	White balance brightness 3500cd/m²; Automatically adjust and manually adjust according to ambient brightness
Viewing Angle	Horizontal 160, Vertical 140					
Display	1.8mm		1.5mm			
Scanning	16 scans		16 scans		13 scans	
Average	≥ 100000 hours					
Gray Scale	≥16(bit)					
White Field Color	5500K-15000K (adjustable)					
Drive Mode	Dynamic					
Atenuation Rate	2 years below 0.05%					
Lifespan	≥100,000.00 hours					
Maximum Power	640W/ m²					
Average Power Consumption	224W/ m²					
Power Supply Requirements	200V ~ 240V±10%; AC50HZ, three-phase five-wire					
Operation Temperature	-20℃ ~+50℃					
Working Humidity	20% RH ~ 85% RH, no condensation					
Storage Temperature	-20℃ ~+60℃					
Storage	10%RH~85%RH, no condensation					
Installation Method	Wall mount installation, glass adhesive, hanging, stacking, suitable for curved installations, supports cutting to any size					
Packaging Method	Cardboard Case/ Plywood Case / Flight Case					

Declaration: The relevant parameters in the table are updated in real time, and the data is for reference only. No further notice will be given if there are any upgrades.