

LP Framed Series												
Model	LPF3.91-1025×250	LPF3.91-1025×500	LPF3.91-1025×750	LPF3.91-1025×1000	LPF3.91-1200×250	LPF3.91-1200×500	LPF3.91-1200×750	LPF3.91-1200×1000	LPF3.91-1500×250	LPF3.91-1500×500	LPF3.91-1500×750	LPF3.91-1500×1000
Module												
Pixel Pitch	Horizontal: 3.91mm/Vertical: 3.91mm											
Pixel Density	65536dot/ m²											
Visual Transparency	>80%											
Module Size	1025mm × 250mm											
Overall Module Size	1025mm×250mm m×67mm	1025mm×500mm m×67mm	1025mm×750mm m×67mm	1025mm×1000mm m×67mm	1200mm×250mm m×67mm	1200mm×500mm m×67mm	1200mm×750mm m×67mm	1200mm×1000mm m×67mm	1500mm×250mm m×67mm	1500mm×500mm m×67mm	1500mm×750mm m×67mm	1500mm×1000mm mm×67mm
LED Type	2121 (Integrated light drive)											
Weight	2.05kg	3.45kg	4.8kg	6.25kg	2.3kg	3.9kg	5.55kg	7.2kg	2.6kg	4.35kg	6.15kg	7.95kg
Resolution Ratio	256 × 64pix	256 × 128pix	256 × 192pix	256 × 256pix	300 × 64pix	300 × 128pix	300 × 192pix	300 × 256pix	376 × 64pix	376 × 128pix	376 × 192pix	376 × 256pix
LED Control System	Synchronous/Asynchronous											
Brightness	White balance brightness 4000cd/m²; Automatically adjust and manually adjust according to ambient brightness								White balance brightness 3000cd/m²; Automatically adjust and			
Viewing Angle	Horizontal 160, Vertical 140											
Display	1.8mm											
Resumable Transmission	Supported											
Average	≥ 100000 hours											
Gray Scale	≥ 16(bit)											
White Field Color	5500K-15000K (adjustable)											
Drive Mode	Static											
Atenuation Rate	2 years below 0.05%											
Lifespan	≥100,000.00 hours											
Maximum Power	1200W/ m²								960W/ m²			
Average Power Consumption	420W/ m²								336W/ m²			
Power Supply Requirements	110V ~ 220V±10%; AC50HZ, three-phase five-wire											
Operation Temperature	-20℃ ~ +50℃											
Working Humidity	20% RH ~ 85% RH, no condensation											
Storage Temperature	-20℃ ~ +60℃											
Storage	10%RH~85%RH, no condensation											
Installation Method	Wall mount installation, glass adhesive, hanging, stacking, suitable for curved installations, supports cutting to any size											
Packaging Method	Cardboard Case/ Plywood Case / Flight Case											

Declaration: The relevant parameters in the table are updated in real time, and the data is for reference only. No further notice will be given if there are any upgrades.