

# Holographic DualView Series

Double Impact, Infinite Vision

## Application scenarios

- Retail Industry: Shopping mall atrium, Restaurant & Retail shop window
- Business Activities: Conference rooms, Trade fairs, Concerts
- Interactive Entertainment: Enterprise buildings, 4S stores, Amusement parks, Airports, High-speed rail



## Features



One Screen, Dual Sides, Infinite Creativity



Flexible installation,  
free lifting points



Efficient heat dissipation,  
lasting stability



Newly added frame,  
improved damage resistance

See the Unseen Beyond the Screen

Specification

|                                 |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
|---------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Module                          |                             |                                                                                                              |                           |                                                                                                              |                           |                                                                                                              |
| Pixel Pitch                     | Horizontal: 3.91mm/Vertical: 3.91mm                                                                          | Horizontal:2.9mm/Vertical: 2.9mm                                                                             | Horizontal: 3.91mm/Vertical: 3.91mm                                                                          | Horizontal:2.9mm/Vertical: 2.9mm                                                                             | Horizontal: 3.91mm/Vertical: 3.91mm                                                                          | Horizontal:2.9mm/Vertical: 2.9mm                                                                             |
| Pixel Density                   | 65536dot/ m²                                                                                                 | 112896dot/ m²                                                                                                | 65536dot/ m²                                                                                                 | 112896dot/ m²                                                                                                | 65536dot/ m²                                                                                                 | 112896dot/ m²                                                                                                |
| Visual Transparency             | > 80%                                                                                                        |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Module Size                     | 750mm×1200mm                                                                                                 |                                                                                                              | 1000mm×1500mm                                                                                                |                                                                                                              | 750mm×1500mm                                                                                                 |                                                                                                              |
| Overall Module Size             | 783mm×1329.01mm×77.9mm                                                                                       |                                                                                                              | 1033mm×1629mm×77.9mm                                                                                         |                                                                                                              | 783mm×1629mm×77.9mm                                                                                          |                                                                                                              |
| LED Type                        | 2121 (Integrated light drive)                                                                                | 1818 (Integrated light drive)                                                                                | 2121 (Integrated light drive)                                                                                | 1818 (Integrated light drive)                                                                                | 2121 (Integrated light drive)                                                                                | 1818 (Integrated light drive)                                                                                |
| Resolution Ratio                | 192×300pix                                                                                                   | 252×392pix                                                                                                   | 256×376pix                                                                                                   | 336×492pix                                                                                                   | 192×376pix                                                                                                   | 252×492pix                                                                                                   |
| LED Control System              | Synchronous/Asynchronous                                                                                     |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Brightness                      | White balance brightness ≥3500cd/㎡; Automatically adjust and manually adjust according to ambient brightness | White balance brightness ≥2000cd/㎡; Automatically adjust and manually adjust according to ambient brightness | White balance brightness ≥3500cd/㎡; Automatically adjust and manually adjust according to ambient brightness | White balance brightness ≥2000cd/㎡; Automatically adjust and manually adjust according to ambient brightness | White balance brightness ≥3500cd/㎡; Automatically adjust and manually adjust according to ambient brightness | White balance brightness ≥2000cd/㎡; Automatically adjust and manually adjust according to ambient brightness |
| Viewing Angle                   | Horizontal 160, Vertical 140                                                                                 |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Display Thickness               | 3.6mm                                                                                                        | 3mm                                                                                                          | 3.6mm                                                                                                        | 3mm                                                                                                          | 3.6mm                                                                                                        | 3mm                                                                                                          |
| Resumable Transmission          | Supported                                                                                                    |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Average Lifespan                | ≥ 100000 hours                                                                                               |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Gray Scale                      | ≥16(bit)                                                                                                     |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| White Field Color Temperature   | 5500K-15000K (adjustable)                                                                                    |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Drive Mode                      | Static                                                                                                       |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Attenuation Rate                | 2 years below 0.05%                                                                                          |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Average Fault-Free Working Time | ≥ 10000 hours                                                                                                |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Maximum Power Consumption       | 1335W/ m²                                                                                                    | 865w/㎡                                                                                                       | 1335W/ m²                                                                                                    | 865w/㎡                                                                                                       | 1335W/ m²                                                                                                    | 865w/㎡                                                                                                       |
| Average Power                   | 534W/ m²                                                                                                     | 340w/㎡                                                                                                       | 534W/ m²                                                                                                     | 340w/㎡                                                                                                       | 534W/ m²                                                                                                     | 340w/㎡                                                                                                       |
| Power Supply Requirements       | 110V ~ 220V±10%; AC50HZ, three-phase five-wire                                                               |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Operation Temperature           | -20℃ ~ +50℃                                                                                                  |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Working Humidity                | 20% RH ~ 85% RH, no condensation                                                                             |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Storage Temperature             | -20℃ ~+60℃                                                                                                   |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Storage Humidity                | 10%RH~ 85%RH, no condensation                                                                                |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Installation Method             | Vertical                                                                                                     |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |
| Packaging Method                | Cardboard Case/ Plywood Case / Flight Case                                                                   |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |                                                                                                              |

Declaration: The relevant parameters in the table are updated in real time, and the data is for reference only. No further notice will be given if there are any upgrades.

